

# Canvas Windows

## TECHNICAL SPECIFICATION

Material	Aluminium Alloy
Alloy and Temper	HE9 WP (6063 T5/T6)
Aluminium Sections	Factory made virgin Aluminium Profile
Powder Coating Make	Jotun/Akzonobel
Powder Coating Thickness	60-80 microns
Glass Make	Saint Gobain/Asahi
Glass Thickness and Type	0.005m Thick Clear Float
Flymesh	SS type 304 grade
Flymesh Thickness	0.00022m
Roller	PVC
Push Handle	Powder Coated Aluminium
Flymesh Roller	PVC
Flymesh Handle	Powder Coated Aluminium
Anti-lifter	PVC
Anti-lifter Cover	PVC
U Guide Glass Shutter	PVC
U Guide Mesh Shutter	PVC
Aluminium Cleats	Aluminium die cast for easy joint with button
Screws for L-cleats	SS 304 (0.006x0.013)m
Wall Fixing Screws	SS 304 (0.01x0.1)m
Sleeve For Screws	PVC (0.008x0.035)m
Gasket	EPDM (Ethylene Propylene Diene Monomer) Best Suitable For Sun Light And Water
L-clips for Shutter Corner	Galvanised Iron
Thickness	0.008m - 0.001m

Tolerance will be as per IS:3965-1981